nextek 281

Microencapsulated Phase Change Material Phase Change: 28°C, 82.4°F

DESCRIPTION

nextek is the next level in PCM technology and performance. Nextek's patented capsule wall technology combines robustness, high thermal stability, and easy dispersability. It is versatile enough to be used in a variety of uses and formulations.

APPLICATIONS

The applications for phase change materials are limited only by the imagination. Some common uses for nextek PCM at this temperature include:

- **Bedding** to provide desired human comfort requirements such as a cool touch effect to mattresses, pillows, and mattress ticking.
- Building Materials to increase the energy efficiency of residential and commercial buildings.
- Consumer Textiles to provide desired human comfort requirements such as cool touch effect to fabrics or the ability to keep people cool when material is worn close to the body. nextek has helped companies achieve Oeko-Tex[®] Standard 100 Class I certification.

PACKAGING

This product is generally shipped in either 55-gallon fi ber drums of 245 pounds net weight (191 pounds dry weight) or in super sacks of 1,000 pounds (approximately 780 pounds dry weight).

PROPERTIES

nextek 28I typically exhibits these general properties:

Typical Properties	
Appearance	White to slightly off-white color
Form	Wet cake (≥ 78% solids)
Particle size (mean)	14-24 micron
Melting point	28°C, 82.4°F (±2°C)
Heat of fusion	∼185 J/g (minimum ≥175 J/g)

HEALTH AND SAFETY

Please refer to the Safety Data Sheet (SDS) for necessary safety and handling precautions for this product.

Visit **www.microteklabs.com** or call **937.236.2213** for more information on your thermal management needs.

IMPORTANT NOTE: This data has been compiled from testing that Microtek Labs believes reliable and is supplied for informational purposes only. Microtek Labs encourages purchasers to validate this data and the product's fitness for use in the purchaser's process by performing their own tests.

MT18_002 Nextek 28W PDS © 2022 Microtek Laboratories, Inc. All Rights Reserved. All other trademarks are the properties of their respective owners.





Revision 4

Effective Date: 12/11/2024